


# Wiha SoftFinish® electric.

The Safe and Comfortable Insulated VDE Screwdriver.



AC 1000V  
IEC 60900:2004



*The insulation is moulded directly onto the blade and cannot be detached from the handle.*



## Wiha SoftFinish® electric:

- Insulation moulded directly onto blade
- Awarded the GS symbol for tested safety
- For all work on or around electrical components up to 1,000 V AC and 1,500 V DC
- Each screwdriver is individually tested in a water bath at 10,000 Volts according to IEC 60900:2004
- Multi-component SoftFinish® handle provides maximum user comfort
- Ergonomically perfect handle design
- Printed screw symbol on handle end for fast identification



*Easily and safely, the high-quality blade insulation protects the user when working with live components.*



*The right tool at a glance, thanks to the printed screw symbol on the handle end.*

## For Slotted and Phillips Screws.



**320N** SoftFinish® electric Slotted Screwdriver.  
Insulation 1,000 V AC, VDE-tested and with GS Mark.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish.  
Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: DIN 7437, DIN ISO 2380.  
Manufactured acc. to IEC 60900:2004.

Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	⌀	→	←	↔	↕	↔
00819 2	2.0	60	0.4	164	23	10
00820 8	2.5	75	0.4	179	23	10
00821 5	3.0	100	0.5	204	23	10
00822 2	3.5	100	0.6	204	23	10
00823 9	4.0	100	0.8	211	30	10
00824 6	4.5•	125	1.0	236	30	10
00825 3	4.5•	175	1.0	286	30	5
31863 5	4.5	200	1.0	311	30	10
00826 0	5.5	125	1.0	243	36	10
00827 7	5.5•	175	1.0	293	36	5
00828 4	6.0•	150	1.2	268	36	10
00829 1	6.5	150	1.2	268	36	10
00830 7	8.0	175	1.2	299	41	10
00831 4	8.0	175	1.6	299	41	10
00832 1	10.0	200	1.6	324	41	10

•Additional dimension. Non-DIN size.



**321N** SoftFinish® electric Phillips Screwdriver.  
Insulation 1,000 V AC, VDE-tested and with GS Mark.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish.  
Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: DIN 7438, DIN ISO 8764.  
Manufactured acc. to IEC 60900:2004.

Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	⊕	→	←	↔	↕	↔
00846 8	PH0	60	164	23		10
00847 5	PH1	80	191	30		10
00848 2	PH2	100	218	36		10
00849 9	PH3	150	268	41		10
00850 5	PH4	200	318	41		5

## For Pozidriv and TORX® Screws.



**324** SoftFinish® electric Pozidriv Screwdriver.  
Insulation 1,000 V AC, VDE-tested and with GS Mark.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish.  
Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: DIN 7438, DIN ISO 8764.  
Manufactured acc. to IEC 60900:2004.

Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	⊕	→	←	↔	↕	↔
00877 2	PZ0	60	164	23		10
00878 9	PZ1	80	191	30		10
00879 6	PZ2	100	218	36		10
00880 2	PZ3	150	324	41		5



**325** SoftFinish® electric TORX® Screwdriver.  
Insulation 1,000 V AC, VDE-tested and with GS Mark.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish.  
Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: Manufactured acc. to IEC 60900:2004.

Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	⊗	→	←	↔	↕	↔
03760 4	T5	60	164	23		10
03761 1	T6	60	164	23		10
03762 8	T7	60	164	23		10
00881 9	T8	60	164	23		10
00882 6	T9	60	164	23		10
00883 3	T10	60	164	23		10
00884 0	T15	80	191	30		10
00885 7	T20	80	191	30		10
00886 4	T25	80	198	36		10
00887 1	T27	100	218	36		10
00888 8	T30	100	218	36		10
00889 5	T40	150	274	41		5
03763 5	T45	150	274	41		5