

Model 5300



- Double molded plastic housing
- CAT III 1000V



EMC & LVD  
EN: 61326  
EN: 61010-1,  
EN: 61010-02-031

**Features**

- Meets IEC10101, CATIII 1000V
- Large dual display with backlight
- Test hold function for easy operation
- Zero Automatic adjustment
- Sampling Rate: 2.5 times per second
- Easy to carry testing package
- Over range Indication
- Low Battery Indication
- Includes 6 "AA" batteries, test leads and carrying case

**Specifications**

	Range	Max Resolution	Accuracy
Earth resistance	10Ω	0.01Ω	±2%rdg ±0.1Ω
	100Ω	0.1Ω	±2%rdg ±3dgt
	1000Ω	1Ω	±2%rdg ±3dgt
Voltage AC	750V	1V	±1.2%rdg ±10dgt
Voltage DC	1000V	1V	±0.8%rdg ±3dgt
Resistance	200kΩ	0.1kΩ	±1.0%rdg ±2dgt
Continuity Test	Active Sound Level: <40Ω, Test current <200mA		
Operating Temp	0°C~40°C(<80%R.H.)		
Storage Temp	-10°C~60°C(<70%R.H.)		
Power Source	1.5V "AA" battery x 6		



Model 5300B



Size(HxWxD): 200mm x 92mm x 50mm

Weight: 582g

Accessories:

Test leads and "AA" Battery x 6, Rubber holster, 4-wire cable and iron rod x 2, gift box with carrying case.

