

## SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/1000V	± (0.5%+2)
AC Voltage	200V/750V	± (0.8%+5)
DC Current	200mA/10A	± (0.8%+5)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/20MΩ	± (0.8%+5)
Temperature (°C)	-40°C~1000°C	± (2%+8)
Frequency	2kHz	± (2%+5)
Duty Cycle	1%~90%	± (4%+5)
<b>Special Functions</b>		
Fused 10A Range		✓
Battery Test	12V	± (3%+5)
Dwell	4Cyl/6Cyl/8Cyl	± (3%+5)
Tach	4Cyl/6Cyl/8Cyl	± (3%+5)
Diode		✓
Continuity Buzzer		✓
Data Hold		✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	Around 10MΩ	✓
Max. Display	1999	✓

## GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	60 x 54 mm
Product Colour	UT107 - Grey, Holster - Red
Product Net Weight	352g
Product Size	179 x 88 x 39 mm
Standard Accessories	Test Lead, Battery, English Manual, Holster, Point Contact Temperature Probe
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	30 pcs
Standard Carton Measurement	490 x 425 x 300 mm (0.062 CBM Per Standard Carton)
Standard Carton Gross Weight	23kg