

## D.C. MILLI-OHM METER



### GOM-801H




### FEATURES

- \* Measures from 20mΩ ~ 20kΩ in 7 Ranges
- \* 1A High Test Current
- \* High Resolution 10 μΩ
- \* Hi/Lo Comparator Indicator and Buzz Alarm
- \* 3 1/2 Digits 0.5" LED Display

### GTL-108A Test Lead

For: GOM-801H/802, GDM-8255A/8251A



The GOM-801H milliohm meter is the ideal device for quick and handy measurement for precise resistance of component and materials. The main display is equipped with 3 1/2 digits 0.5" LED in a distinctive red color. Measurable objects cover cable joints, earth bonds, switches, motors, transformers, generators, and many others. The test range is separated into seven levels between 20mΩ and 20kΩ, accessible from the front panel in a single press. An internal comparator provides a user settable Hi/Lo indication. The GOM-801H is the best way to go for an inexpensive, easy to use, yet reliable milliohm meter.

### SPECIFICATIONS

TEST RANGE	
	20, 200mΩ, 2, 20, 200Ω, 2k, 20kΩ, 7 Ranges
TEST CURRENT (Test Voltage 02V)	
	20mΩ/200mΩ : 1A 2Ω : 0.1A 20Ω : 10mA 200Ω : 1mA 2kΩ : 100μA 20kΩ : 10μA
ACCURACY	
Measuring	20mΩ ± (0.2% rdg + 6 digits) 200mΩ ~ 20kΩ ± (0.2% rdg + 4 digits)
Setting	± (0.2% + 6 digits)
RESOLUTION	
	0.01, 0.1, 1, 10, ( ≥ symbol) 100mΩ, 1, 10
COMPARATOR	
	HI, LO settable
DISPLAY	
	3 1/2 digits 0.5" LED display HI, GO, LO indicator
POWER SOURCE	
	AC 100V/120V/220V/230V±10%, 50/60Hz
DIMENSIONS & WEIGHT	
	230(W) x 95(H)x280(D)mm, Approx. 2 kg

### ORDERING INFORMATION

**GOM-801H** High Precision Programmable DC Milli-Ohm Meter

#### ACCESSORIES :

User manual x 1, Power cord x 1  
Test Lead GTL-108A x 1